

额定电压等级 Rated Voltage Class	变压器类型 Transformer Type	额定 容量 Rated power (KVA)	电压组合 voltage combination			联结组 标号 Conne- ction symbol	产品型号 Product Model	短路阻抗 (%) Short - circuit Impedance (%)
			高压分 接范围 HV tapping range (%)	高压 HV (kV)	低压 LV (kv)			
10KV级 10kV Class	S□-M-3□ 2500KV A 系列液浸式全密封配电变压器 I-III 级能效 Full-sealed Liquid-immersed Distribution Power Transformer Class I-III Energy Efficiency	30-2500	±2x2.5 ±5	6 6.3 10 10.5	0.4	Dyn11 Yyn0	S(B)13 S(B)20 S(B)22	4.0、4.5、5.0
	S□-M·RL-3□ 1000KVA 系列立体卷铁心液浸式配电变压器 I - 级能效 Three Dimensional Wound Core Liquid - Immersed Distribution Power Transformer	30-1000					S(B)13 S(B)20 S(B)22	4.0、4.5
	S13-M·ZT-160 (50)~ 630 (200) kVA 系列有载调容调压配电变压器 S13-M·ZT-160 (50) ~630 (200) kVA On Load Capacity Regulation And Oltc Distribution Power Transformer	160(50)-630(200)	±5	10 10.5 11			—	4.0(4.0)、4.5(4.0)
	S (B) H□-M 系列节能型非晶合金铁心配电变压器 I-III 级能效 Amorphous Alloy Core Energy Saving Distribution Power Transformer Class I-III Energy Efficiency	30 - 1600	±2x2.5 ±5	6 6.3 10 10.5			S(B)H15 S(B)H21 S(B)H25	4.0、4.5
	SZ13 - 20□ 2500KVA 系列双绕组有载调压配电变压器 Double Winding OLTC Distribution Power Transformer	200 - 2500	±4x2.5	6 6.3 10 10.5			—	4.0、4.5、5.0
	硅钢高过载配变 Siliconsteel high overload distribution transformers	50 - 200	±2x2.5 ±5	10 10.5 11			S11 S13	4.0
35KV级 35kV Class	油浸式三相双绕组无励磁调压电力变压器 I - III 级能效 Oil - immersed Three - phase Double Winding Off - circuit Voltage Regulation Power Transformer Class I - III Energy Efficiency	3150 - 31500	±2×2.5 ±5	35~38.5	3.15 3.3 6.3 6.6 10.5	Yd11 YNd11	S18 S20 S22	7、8、10
	油浸式三相双绕组有载调压电力变压器 I-III 级能效 Oil-immersed Three-phase Double Winding OLTC Power Transformer Class I-III Energy Efficiency	3150 - 31500	±3x2.5	35~38.5	6.3 6.6 10.5		S18 S20 S22	7、7.5、8、10
66KV级 66kV Class	油浸式三相双绕组无励磁调压电力变压器 I - III 级能效 Oil - immersed Three - phase Double Winding Off - circuit Voltage Regulation Power Transformer Class I - III Energy Efficiency	3150 - 63000	±2×2.5 ±5	63 66 69	6.3 6.6 10.5	YNd11	S18 S20 S22	8、9
	油浸式三相双绕组无励磁调压电力变压器 I - III 级能效 Oil - immersed Three - phase Double Winding Off - circuit Voltage Regulation Power Transformer Class I - III Energy Efficiency	6300 - 63000	±8×1.25				S18 S20 S22	9
110KV级 110kV Class	油浸式三相双绕组无励磁调压电力变压器 级能效 I - III Oil - immersed Three - phase Double Winding Off - circuit Voltage Regulation Power Transformer Class I - III Energy Efficiency	6300 - 180000	±2×2.5	110 115 121	6.3 6.6 10.5 13.8 15.75 18 21	YNd11	S18 S20 S22	10.5、12~14
	油浸式三相双绕组低压为 35KV 无励磁调压电力变压器 级能效 I - III Oil - immersed Three - phase Double Winding Off - circuit Voltage Regulation Power Transformer Class I - III Energy Efficiency	6300 - 63000	±2×2.5		36 37 38.5		S18 S20 S22	10.5
	油浸式三相双绕组无励磁调压电力变压器 级能效 I - III Oil - immersed Three - phase Three - winding Off - circuit Voltage Regulation Power Transformer Class I - III Energy Efficiency	6300 - 63000	±2×2.5			YNynod11	S18 S20 S22	升压 高 - 中 17.5~18.5 高 - 低 10.5 中 - 低 6.5 降压 高 - 中 10.5 高 - 低 18~19 中 - 低 6.5 Boosting High - Medium: 17.5 - 18.5 High - Low: 10.5 Medium - Low: 6.5 Step - down High - Medium: 10.5 High - Low: 18 - 19 Medium - Low: 6.5
	油浸式三相双绕组有载调压电力变压器 I-III 级能效 Oil-immersed Three-phase Double Winding OLTC Power Transformer Class I-III Energy Efficiency	6300 - 63000	±8×2.5	110	6.3 6.6 10.5 21		S18 S20 S22	10.5
	油浸式三相三绕组有载调压电力变压器 I-III 级能效 Oil-immersed Three-phase Triple Winding OLTC Power Transformer Class I-III Energy Efficiency	6300 - 63000	±8×2.5			YNynOd11	S18 S20 S22	高 - 中 10.5 高 - 低 17.5~18.5 中 - 低 6.5 High - Medium: 10.5 High - Low: 17.5 - 18.5 Medium - Low: 6.5

地址：上海市金山区金山工业区亭卫公路 4185 号

电话：+86 15900431111

WhatsApp：+86 15821831910

Add：No. 4185, Tingwei Highway, Jinshan Industrial Zone, Jinshan District, Shanghai

Website：www.zbbtransformer.com

